

doscan ASM

Version: 4 / GB

Replaces Version: 3 / GB

Date revised: 06.09.2023

Print date: 11.09.23

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

doscan ASM

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified Uses

PC35

Washing and cleaning products (including solvent based products)

1.3. Details of the supplier of the safety data sheet

Address:

Chemische Fabrik Dr. Weigert GmbH & Co. KG

Mühlenhagen 85

D-20539 Hamburg

Telephone no.

+49 40 789 60 0

Fax no.

+49 40 789 60 120

www.drweigert.com

E-mail address of person responsible for this SDS:

sida@drweigert.de

1.4. Emergency telephone number

Emergency telephone number: 112

SECTION 2: Hazards identification ***

2.1. Classification of the substance or mixture

Classification (Regulation (EC) No. 1272/2008)

Classification (Regulation (EC) No. 1272/2008)

Flam. Liq. 2 H225

Eye Irrit. 2 H319

STOT SE 3 H336

*

*

*

The product is classified and labelled in accordance with Regulation (EC) No 1272/2008
For explanation of abbreviations see section 16.

2.2. Label elements

Labelling according to regulation (EC) No 1272/2008

Hazard pictograms



Signal word

Danger

doscan ASM

Version: 4 / GB

Replaces Version: 3 / GB

Date revised: 06.09.2023

Print date: 11.09.23

Hazard statements

H225 Highly flammable liquid and vapour.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313 If eye irritation persists: Get medical advice/attention.
Dispose only when container is empty and closed. For disposal of product residues, refer to safety data sheet.

Hazardous component(s) to be indicated on label (Regulation (EC) No. 1272/2008)

contains *** propan-2-ol

2.3. Other hazards

No special hazards have to be mentioned.
The product contains no PBT substances. The product contains no vPvB substances. This product does not contain a substance that has endocrine disrupting properties with respect to human. The product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms.

SECTION 3: Composition/information on ingredients ***

3.2. Mixtures

Hazardous ingredients ***

propan-2-ol

CAS No.	67-63-0				
EINECS no.	200-661-7				
Registration no.	01-2119457558-25				
Concentration	>= 25	<	50	%	
Classification (Regulation (EC) No. 1272/2008)	Flam. Liq. 2				H225
	Eye Irrit. 2				H319
	STOT SE 3				H336

Other information

Complete text of hazard statements in chapter 16

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated clothing immediately and dispose of safely. In case of persistent symptoms consult doctor.

After inhalation

Ensure supply of fresh air. Seek medical advice immediately.

After skin contact

Wash off immediately with soap and water. Seek medical advice immediately.

doscan ASM

Version: 4 / GB

Replaces Version: 3 / GB

Date revised: 06.09.2023

Print date: 11.09.23

After eye contact

Separate eyelids, wash the eyes thoroughly with water (15 min.). Seek medical advice immediately.

After ingestion

Call in a physician immediately and show him the Safety Data Sheet.

Adhere to personal protective measures when giving first aid

First aider: Pay attention to self-protection!

4.2. Most important symptoms and effects, both acute and delayed

Until now no symptoms known so far.

4.3. Indication of any immediate medical attention and special treatment needed

Hints for the physician / hazards

In the case of swallowing with subsequent vomiting, aspiration of the lungs can occur which can lead to chemical pneumonia or asphyxiation.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Dry powder, Foam, Carbon dioxide, Water spray jet

Non suitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

In case of combustion evolution of dangerous gases possible.

5.3. Advice for firefighters

Special protective equipment for fire-fighting

Do not inhale explosion and/or combustion gases. In case of combustion use a suitable breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Keep away sources of ignition. Ensure adequate ventilation. Use personal protective clothing.

6.2. Environmental precautions

Prevent spread over a wide area (e.g. by containment or oil barriers). Do not discharge into the drains/surface waters/groundwater. Do not discharge into the subsoil/soil.

6.3. Methods and material for containment and cleaning up

Pick up rest with suitable absorbent materials. Containers in which spilt substance has been collected must be adequately labelled. Dispose of as prescribed.

6.4. Reference to other sections

Refer to protective measures listed in Sections 7 and 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Use only in well-ventilated areas.

Advice on protection against fire and explosion

Keep away from sources of heat and ignition. No smoking. Take action to prevent static discharges.

doscan ASM

Version: 4 / GB

Replaces Version: 3 / GB

Date revised: 06.09.2023

Print date: 11.09.23

7.2. Conditions for safe storage, including any incompatibilities

Recommended storage temperature

Value > -20 < 30 °C

Requirements for storage rooms and vessels

Store product in closed containers.

Hints on storage assembly

Do not store with strong oxidizing agents.

Storage classes

Storage class according to TRGS 510 3 Flammable liquid

Further information on storage conditions

Keep container tightly closed. Keep container in a cool, well-ventilated place. Protect from heat and direct sunlight.

7.3. Specific end use(s)

no data

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limit values

propan-2-ol

List	EH40			
Type	WEL			
Value	999	mg/m ³	400	ppm(V)
Short term exposure limit	1250	mg/m ³	500	ppm(V)

Other information

There are not known any further control parameters.

8.2. Exposure controls

General protective and hygiene measures

Do not smoke during work time. Do not inhale gases/vapours/aerosols. Do not eat or drink during work time. Take off immediately all contaminated clothing. Wash hands before breaks and after work.

Respiratory protection

If workplace limits are exceeded, a respiratory protection approved for this particular job must be worn. Short term: filter apparatus, Filter A

Hand protection

Chemical resistant gloves			
Use	Permanent hand contact		
Appropriate Material	butyl		
Material thickness	>=	0,7	mm
Breakthrough time	>	480	min
Appropriate Material	nitrile		
Material thickness	>	0,4	mm
Breakthrough time	>	120	min
Use	Short-term hand contact		
Appropriate Material	nitrile		
Material thickness	>	0,28	mm
Hand protection must comply with EN ISO 374.			

Eye protection

Safety glasses with side protection shield; Eye protection must comply with EN 166.

doscan ASM

Version: 4 / GB

Replaces Version: 3 / GB

Date revised: 06.09.2023

Print date: 11.09.23

Body protection

Clothing as usual in the chemical industry.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	liquid
Colour	colourless
Odour	characteristic
Melting point	
Remarks	not determined
Freezing point	
Remarks	not determined
Boiling point or initial boiling point and boiling range	
Remarks	not determined
Flammability	
evaluation	not determined
Upper and lower explosive limits	
Remarks	not determined
Flash point	
Value	17 to 21 °C
Method	closed cup
Ignition temperature	
Remarks	not determined
Decomposition temperature	
Remarks	not determined
pH value	
Value	appr. 7,3
Temperature	20 °C
Viscosity	
Remarks	not determined
Solubility(ies)	
Remarks	not determined
Partition coefficient n-octanol/water (log value)	
Remarks	not determined
Vapour pressure	
Remarks	not determined
Density and/or relative density	
Value	0,96 g/cm ³
Temperature	20 °C
Relative vapour density	
Remarks	not determined
9.2. Other information	
Odour threshold	
Remarks	not determined

doscan ASM

Version: 4 / GB

Replaces Version: 3 / GB

Date revised: 06.09.2023

Print date: 11.09.23

Evaporation rate (ether = 1) :

Remarks not determined

Solubility in water

Remarks miscible in all proportions

Explosive properties

evaluation not determined

Oxidising properties

evaluation None known

Other information

None known

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reactions when stored and handled according to prescribed instructions.

10.2. Chemical stability

No hazardous reactions known.

10.3. Possibility of hazardous reactions

No hazardous reactions known.

10.4. Conditions to avoid

No hazardous reactions known. Evolution of flammable mixtures possible in air when heated above flash point and/or during spraying or misting.

10.5. Incompatible materials

Reactions with strong oxidising agents.

10.6. Hazardous decomposition products

No hazardous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity

Species	rat	
LD50	> 2000	mg/kg
Method	calculated value (Regulation (EC) No. 1272/2008)	
Remarks	Based on available data, the classification criteria are not met.	

Acute oral toxicity (Components)

propan-2-ol

Species	rat	
LD50	5840	mg/kg
Method	OECD 401	

Acute dermal toxicity

Remarks Based on available data, the classification criteria are not met.

Acute dermal toxicity (Components)

propan-2-ol

Species	rabbit	
LD50	13900	mg/kg
Method	OECD 402	

Acute inhalational toxicity

doscan ASM

Version: 4 / GB

Replaces Version: 3 / GB

Date revised: 06.09.2023

Print date: 11.09.23

Remarks Based on available data, the classification criteria are not met.

Acute inhalative toxicity (Components)

propan-2-ol

Species	rat		
LC50	>	25	mg/l
Duration of exposure	6	h	
Administration/Form	Vapors		
Method	OECD 403		

Skin corrosion/irritation

Remarks Based on available data, the classification criteria are not met.

Serious eye damage/irritation

evaluation	irritant
Remarks	The classification criteria are met.

Sensitization

Remarks Based on available data, the classification criteria are not met.

Subacute, subchronic, chronic toxicity

Remarks Based on available data, the classification criteria are not met.

Mutagenicity

Remarks Based on available data, the classification criteria are not met.

Reproductive toxicity

Remarks Based on available data, the classification criteria are not met.

Carcinogenicity

Remarks Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity (STOT)

Single exposure

evaluation	May cause drowsiness or dizziness.
Remarks	The classification criteria are met.

Repeated exposure

Remarks Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Endocrine disrupting properties with respect to humans

The product does not contain a substance that has endocrine disrupting properties with respect to humans.

Other information

There is no data available on the product apart from the information given in this subsection.

SECTION 12: Ecological information

12.1. Toxicity

General information

not determined

Fish toxicity (Components)

propan-2-ol

Species	Fathead minnow (<i>Pimephales promelas</i>)
LC50	9640 mg/l

doscan ASM

Version: 4 / GB

Replaces Version: 3 / GB

Date revised: 06.09.2023

Print date: 11.09.23

Duration of exposure 96 h

Daphnia toxicity (Components)

propan-2-ol

Species	Daphnia magna	
LC50	appr. 10000	mg/l
Duration of exposure	48	h

Algae toxicity (Components)

propan-2-ol

Species	Scenedesmus subspicatus	
IC50	> 1000	mg/l
Duration of exposure	72	h

Bacteria toxicity (Components)

propan-2-ol

Species	activated sludge	
EC50	> 100	mg/l

12.2. Persistence and degradability

General information

There is no data available on the product apart from the information given in this subsection.

12.3. Bioaccumulative potential

General information

There is no data available on the product apart from the information given in this subsection.

Partition coefficient n-octanol/water (log value)

Remarks not determined

12.4. Mobility in soil

General information

For this subsection there is no ecotoxicological data available on the product as such.

12.5. Results of PBT and vPvB assessment

General information

Not applicable

Results of PBT and vPvB assessment

The product contains no PBT substances
The product contains no vPvB substances.

12.6 Endocrine disrupting properties

Endocrine disrupting properties with respect to the environment

The product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms.

12.7. Other adverse effects

General information

not determined

General information / ecology

The surfactant(s) contained in this preparation complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents. Do not discharge product unmonitored into the environment.

SECTION 13: Disposal considerations

doscan ASM

Version: 4 / GB

Replaces Version: 3 / GB

Date revised: 06.09.2023

Print date: 11.09.23

13.1. Waste treatment methods

Disposal recommendations for the product

EWC waste code 18 01 06* chemicals consisting of or containing dangerous substances

EWC waste code 20 01 29* detergents containing dangerous substances

The listed waste code numbers, according to the European Waste Catalogue (EWC), are to be understood as a recommendation. A final decision must be made in agreement with the regional waste disposal company.

Disposal recommendations for packaging




EWC waste code 15 01 02 plastic packaging

Completely emptied packagings can be given for recycling.

EWC waste code 15 01 10* packaging containing residues of or contaminated by dangerous substances

Packaging that cannot be cleaned should be disposed of in agreement with the regional waste disposal company.

SECTION 14: Transport information

	Land transport ADR/RID	Marine transport IMDG/GGVSee	Air transport ICAO/IATA
Tunnel restriction code	D/E		
IMDG-Code segregation group		0 Not applicable	
14.1. UN number or ID number	1987	1987	1987
14.2. UN proper shipping name	ALCOHOLS, N.O.S. Solution (propan-2-ol)	ALCOHOLS, N.O.S. Solution (propan-2-ol)	ALCOHOLS, N.O.S. Solution (propan-2-ol)
14.3. Transport hazard class(es)	3	3	3
Label			
14.4. Packing group	II	II	II
Special provision	640D		
Limited Quantity	1 I	1 I	
Transport category	2		
14.5. Environmental hazards		no	

Information for all modes of transport

14.6. Special precautions for user

See Sections 6 to 8

Other information

14.7 Maritime transport in bulk according to IMO instruments

Not applicable

doscan ASM

Version: 4 / GB

Replaces Version: 3 / GB

Date revised: 06.09.2023

Print date: 11.09.23

SECTION 15: Regulatory information ***

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Major-accident categories acc. 2012/18/EU ***

Category	P5b	FLAMMABLE LIQUID	50	tonne	200	tonne
				s		s

Ingredients (Regulation (EC) No 648/2004)

30 % and more:

non-ionic surfactants

less than 5 %:

aliphatic hydrocarbons

Water Hazard Class (Germany)

Water Hazard Class (Germany) WGK 1

Remarks Derivation of WGK according to Annex 1 No. 5.2 AwSV

VOC

VOC (EU) 0 %

Other information

The product does not contain substances of very high concern (SVHC).

15.2. Chemical safety assessment

For this preparation a chemical safety assessment has not been carried out.

SECTION 16: Other information

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Classification (Regulation (EC) No. 1272/2008)	
Flam. Liq. 2	H225
Eye Irrit. 2	H319
STOT SE 3	H336

Hazard statements listed in Chapter 2/3

H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

CLP categories listed in Chapter 2/3

Eye Irrit. 2	Eye irritation, Category 2
Flam. Liq. 2	Flammable liquid, Category 2
STOT SE 3	Specific target organ toxicity - single exposure, Category 3

Abbreviations

ADR: Accord européen relatif au transport international des marchandises Dangereuses par Route
RID: Règlement concernant le transport international ferroviaire de marchandises dangereuses
IMDG: International Maritime Code for Dangerous Goods
ICAO: International Civil Aviation Organization
IATA: International Air Transport Association
MARPOL 73/78: International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978 (MARPOL: Marine Pollution)
IBC: Intermediate Bulk Container
CAS: Chemical Abstracts Service

doscan ASM

Version: 4 / GB

Replaces Version: 3 / GB

Date revised: 06.09.2023

Print date: 11.09.23

VOC: Volatile Organic Compound
LD: Lethal dose
LC: Lethal concentration
PBT: Persistent, Bioaccumulative and Toxic
vPvB: Very persistent and very bioaccumulative
SVHC: Substances of very high concern
EU: European Union

Supplemental information

Relevant changes compared with the previous version of the safety data sheet are marked with: ***
This information is based on our present state of knowledge. However, it should not constitute a guarantee for any specific product properties and shall not establish a legally valid relationship.